
GB - RTG,22.2

Model code: 58TC6111X3L6

Print date: 30/11/2016 Last updated: 29/11/2016

Grid Number: 2423456 from 30/11/2016

# **MASTER 3T5 PLATF STD FWD 170E6 - GVW 3.50 T/**





# **WEIGHTS**

| Wheelbase                   |                                  | mm      | 4.332               |  |  |
|-----------------------------|----------------------------------|---------|---------------------|--|--|
| Kerb Weight                 | total                            | Kg 1857 |                     |  |  |
| Changia and karb waight     | Front axles (Liftable axle down) | Kg      | 1359                |  |  |
| Chassis cab kerb weight     | Rear axles (Liftable axle down)  | Kg      | 498                 |  |  |
| Payload                     | (C)                              | Kg      | 1643                |  |  |
|                             | Front axle(s)                    | Kg      | 1857<br>1359<br>498 |  |  |
| Maximum Weight (registered) | Rear axle(s)                     | Kg      | 2100                |  |  |
|                             | Total (GVW)                      | Kg      | 3500                |  |  |

This table includes the weights of the RENAULT TRUCKS options: full urea tank, oil, screen wash fluid and coolant at 100%, fuel fill level 90% and driver present (75kg).

# **LENGTHS**

| Wheelbase              |                        | mm | 4.332 |
|------------------------|------------------------|----|-------|
|                        | (F / BEP L011)         | mm | 4332  |
| Body length            | Max. (Wmax / BEP L105) | mm | 4926  |
| Body length            | Min. (Wmin / BEP L105) | mm | 3741  |
| Max Overall Length (Z) | (Zmax / BEP L001)      | mm | 7364  |
| Min Overall Length (Z) | (Zmin / BEP L001)      | mm | 6180  |
| Doduwerk roor everbone | Max. (Xmax / BEP L017) | mm | 2190  |
| Bodywork rear overhang | Min. (Xmin / BEP L017) | mm | 1006  |
| Overall Chassis Length | (A / BEP L032+L016)    | mm | 6180  |
| Front Overhang         | (H / BEP L016)         | mm | 842   |
| Cab entry              | (B / BEP L102)         | mm | 1596  |

# **HEIGHTS**

| Wheelbase               |                       | mm | 4.332 |
|-------------------------|-----------------------|----|-------|
| Cab height (unladen)    | (0)                   | mm | 2264  |
| Cround algeronge laden  | Front (U1 / BEP H015) | mm | 166   |
| Ground clearance, laden | Rear (U3 / BEP H016)  | mm | 166   |

# **WIDTHS**

| Wheelbase      |                          | mm | 4.332 |
|----------------|--------------------------|----|-------|
| Track          | Front (V1 / BEP W013.1)  | mm | 1750  |
| Track          | Rear 1 (V2 / BEP W013.2) | mm | 1730  |
| Max. cab width | (BEP W002)               | mm | 2070  |

# **OTHER**

| Wheelbase      |                    | mm | 4.332 |
|----------------|--------------------|----|-------|
| Turning Radius | Overall (BEP W012) | mm | 8100  |

#### **M9T ENGINE**

Maximum Power: 125 kW at 3500 rpm

Maximum Torque: 380 Nm from 1500 to 2750 rpm

Power output (UK): 170 hp

Diesel 4-cylinder in-line with high-pressure Common Rail direct diesel injection (2000 bar)

Bore 85 mm - Stroke 101.3 mm - Capacity 2.3 litres.

Cooled air inlet

Water-cooled twin turbochargers on exhaust

Cooled EGR system Chain-driven timing

Direction of rotation (seen from gearbox end): anti-clockwise

Cooling circuit capacity: 9.7 litres. Antifreeze coolant type D, -25° C

Diesel Particulates filter. Catalytic converter.

SCR post-treatment system with AdBlue injection controlled electronically.

Euro 6 pollution control standard

# **ENGINE EQUIPMENT**

ECO mode, engine mapping and torque control and optimisation of temperature comfort settings Stop & Start system
Without engine Power Take Off.

Speed limiter (110 km/h)

#### **CLUTCH**

Single disc dry clutch, diameter 260mm

#### **GEARBOX**

PF6 gearbox, 6 synchronised forward gears and 1 reverse Aluminium casing

# **POWER TAKE-OFFS**

Without gearbox mounted PTO

# **STEERING**

Right hand drive.

Retractable rack and pinion steering: collapsible steering in case of impact

Electric hydraulic pump

# FRONT AXLE ASSEMBLY

Independent wheels.

Lower wishbone.

MacPherson suspension system.

Maximum load on front axle 1850 kg.

Transmission to front wheels by 2 shafts each with 2 constant velocity joints.

# **REAR AXLE ASSEMBLY**

Rigid tubular axle guided by leaf springs. Max. technical capacity: 2100 kg

# WHEELS AND TYRES

225/65 R16 tyres (215/70 for Export). J 6.5 wheels. 16" wheel.

(Tyre make depending on availability).

Single wheel fitment.

Standard wheel trims

Spare wheel

Spare wheel carrier under body with winch.

#### **BRAKING**

#### Service brake:

Disc brakes: 302x28 ventilated at the front, 305x12 at the rear.

ABS Anti-lock Braking System (generation 8.2).

Emergency braking assist (AFU).

ESP trajectory control regulated according to vehicle load,

integrating ASR Hill Start Assist

Trailer trajectory control

# CAB

# Cab exterior:

All steel Cab, electro-zinc plated and cataphoretic paint treatment.

Platform Cab version.

Cab paint colour: WHITE Glacier

Height H1.

Bonnet lift to give access to oil dipstick, windscreen washer bottles, cooling and brake fluid reservoirs plus the offset battery terminals.

Anthracite grained front protective moulding.

2 heated, remote control rear view mirrors with integral indicator lights.

Standard rearview mirror arms.

Front access by anti-slip step

Windscreen access steps integrated into front bumper Tinted, laminated windscreen.

#### Cab interior:

Equipment level "Comfort". Cab 2/3-seats. Upper console storage areas

FM/AM digital radio (DAB)

Smartphone Bluetooth connectivity via AHA specific interface available from the Apple Store and Google Play(Android), In-call navigation/telephone volume mixing, Independent volume adjustment (Navigation/Telephone/Media),

Without tachograph

Driver's seat with lumbar adjustment.

3-point dynamic seat belts with effort limiter for driver and front passengers plus pre-tensioner for driver, height adjustable.

3-point 3rd passenger seat belt.

Passenger double seat

Folding central seat backrest with fold-up shelf

Lifting driver's armrest

KALIENDO seat upholstery

Driver's airbag.

Grab handle for front passengers.

Opening of the doors controls the courtesy light and sets off audible alert if light left on.

Driver's window with impulse control.

Adjustable 4-speed, 6 positions, heater/ defroster for windscreen and front side window demisting.

Air conditioning unit

Driving compartment filter, anti-pollen

Manual in English

Full width bulkhead partition between cab and load area.

3-position front windscreen wiper/windscreen washer.

# Steering wheel equipment:

Steering wheel satellite control for radio and telephone Cruise control and speed limiter controls Adjustable steering column.

# **Instrument panel:**

Fully equipped instrument panel including:

Refrigerated glove box

Gear lever on dashboard.

On-board computer (oil level, mileometer and odometer. Quantity of fuel used. Average consumption in miles per gallon, range on remaining fuel, average speed since last update.

MediaNav with 7" colour touch screen and integrated USB socket, 2D/3D navigation, Danger Zone display, RDS-TMC Traffic Info, voice recognition, 31 languages available On vehicle handover, on Renault Trucks internet site, updates are free for the first 3 months

National mapping

Two central air vents and two direction adjustable side air vents, adjustable flow

Remote control central door locking.

Automatic door-locking when vehicle moves off. 3rd key

2-button key

Cruise control with speed limiter with steering wheel controls Rational driving aid.

# **ELECTRICAL EQUIPMENT**

Battery 12 Volts - 110 Ah. - located in LH stepwell

Alternator: 185 amp capacity.

Halogen headlights.

Direction indicators integrated into headlight units.

Automatic windscreen wiping with rain sensor

Automatic lights

Headlamp adjustment device on dashboard.

Front fog lights.

Two wide-angle reversing lights and one rear fog light. Wiring for supplementary adaptation.

Wiring for camper van or Platform cab adaptation.

The more powerful side marker lamps (84W) option is mandatory on vehicles over 6m long.

# **CHASSIS**

Short rear overhang.

GVW = 3.5T / GCW = 6T

=>Maximum trailer weight: 2500 kg

Front mud flaps.

#### SUSPENSION

# Front suspension

Helical suspension springs. Hydraulic, telescopic shock absorbers.

# Rear suspension:

Air suspension with remote control

Max. travel: +55/-70

Axle chock to maintain an attitude above 0 when laden

#### **FUEL TANK**

Main fuel tank capacity: 105 litres

Secured access to fuel and AdBlue filler flaps

# **AdBlue**

22-litre plastic AdBlue tank

# STANDARD EQUIPMENT

Jack.

Tool kit under driver's seat.

Towing yoke.

#### **BODYWORK**

Bodybuilder adaptation box (BOIADP), for retrieving information on the multiplex network.

Pre-equipment for bodybuilder unit connection (CABADP) including 2 possible connectors on the fascia panel and in the cab. These connectors obtain engine running signal, activate the fast idle and provide electrical power.

# **SPECIAL OPTIONS**

PDI & Factory Delivery
Keyless Running System
Handbrake Interlock
Reverse Camera & 7" Colour Screen
Forward Facing Camera
Tempearature Retaining Curtain
Temperature Warning System
Racking Conversion
Climate Control System
Aerodynamoic Luton Van Conversion
Transfer Microlise Equipment
Signwriting

Thermal Insulation & Roof Vent

# **GEARBOX RATIOS**

| 1    | 2    | 3    | 4    | 5    | 6    |
|------|------|------|------|------|------|
| 4.18 | 2.11 | 1.29 | 0.90 | 0.71 | 0.60 |

The manufacturer reserves the right to modify the specifications above without prior notice. Non contractual document.

For further assistance please contact Product Applications at Renault Trucks UK Limited, Wedgnock Lane, Warwick, CV34 5YA Telephone+44 (0)1926 475333.

# MEDIANAV 2.0

- Last system MediaNav 2.0 allows an easy access to large services through a large 7-inch touchscreen (800\*480 : 18-cm) :
  - Radio: Analog and Digital (Digital Audio Broadcasting)
  - Media by Bluetooth®, Jack and USB plugs to play music through another device.
  - Phone by hands-free Bluetooth® system able to pair up to 5 phones and send or receive calls.
  - Map and GPS navigation Nav&Go® (2D or 3D).
  - Smartphone connectivity by AHA® application for Apple & Android (Web radio, Podcasts, Social media, News)
  - Rear view camera display if option is installed



#### Appreciate the ergonomics

Easily find the MediaNav features thanks to the streamlined ergonomics. When the vehicle is stopped, use the touchscreen, while driving, the steering column controls.

DEPARTMENT AUTHOR NAME



#### Experience built-in navigation

With the built-in navigation, drive with complete peace of mind thanks to intuitive, reliable mapping.



Let the music play

With MediaNav, you can listen to the radio or play your own music by connecting your device to the AUX or USB sockets.

